

## Contact insert - HC-M-PN3-1,60-BU-V - 1663543

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

Pneumatics socket with valve, for HC-M-PN3 module, cross section of hose 1.6 mm



The illustration shows versions, pneumatic male, female and female with valve

### Key commercial data

Packing unit	1 pc
GTIN	 4 017918 123352
Weight per Piece (excluding packing)	0.96 GRM
Custom tariff number	85369010
Country of origin	Germany

### Technical data

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 125 °C
---------------------------------	-------------------

#### Mechanical characteristics

Operating pressure, vacuum	8.00 bar
Internal diameter of pressure hose connection	1.6 mm
Insertion/withdrawal cycles	≥ 500

#### General

Color	black
-------	-------

#### Material data

Contact material	Delrin acetal
------------------	---------------

# Contact insert - HC-M-PN3-1,60-BU-V - 1663543

## Classifications

### eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27140816
eCl@ss 5.0	27143424
eCl@ss 5.1	27143424
eCl@ss 6.0	27143424
eCl@ss 7.0	27440209
eCl@ss 8.0	27440209

### ETIM

ETIM 2.0	EC000796
ETIM 3.0	EC000796
ETIM 4.0	EC000796
ETIM 5.0	EC000796

### UNSPSC

UNSPSC 6.01	30211808
UNSPSC 7.0901	39121408
UNSPSC 11	39121408
UNSPSC 12.01	39121408
UNSPSC 13.2	39121408

## Approvals

### Approvals

---

Approvals

GOST

---

Ex Approvals

---

Approvals submitted

---

Approval details

## Contact insert - HC-M-PN3-1,60-BU-V - 1663543

### Approvals

