



PIN OUT

| DVI29F | DVI29F | DVI29F | DVI29F |
|--------|--------|--------|--------|
| P1 | P2 | P1 | P2 |
| 1 | 1 | 16 | 16 |
| 2 | 2 | 17 | 17 |
| 3 | 3 | 18 | 18 |
| 4 | 4 | 19 | 19 |
| 5 | 5 | 20 | 20 |
| 6 | 6 | 21 | 21 |
| 7 | 7 | 22 | 22 |
| 8 | 8 | 23 | 23 |
| 9 | 9 | 24 | 24 |
| 10 | 10 | C1 | C1 |
| 11 | 11 | C2 | C2 |
| 12 | 12 | C3 | C3 |
| 13 | 13 | C4 | C4 |
| 14 | 14 | C5 | C5 |
| 15 | 15 | SHELL | SHELL |

Electrical Character:

1. Insulation resistance: 5M OHM (Min).
2. Conductive resistance: 2 OHM (Max).
3. With understanding voltage: DC 300V 0.1 SEC.
4. Operating temperature range: -10°C ~ 70°C.

REMARK:

1. CONN: P1, P2 DVI 24+5 FEMALE, PIN: G/F, INSULATION WHITE, NICKEL PLATED SHELL. WITH 2PCS #4-40 NUT.
2. PCB: PCB-E09-180D-A; PCB-E09-180D-B.
3. P1&P2: MOLD BEIGE 25P PVC.
4. CABLE ASS'Y MUST PASS CONTINUITY TEST.
5. MOLD NO.: E09-01, E09-N01.

| C | Add Change molding SIZE | 07/16/15 |
|-----|------------------------------|----------|
| B | ADD THE ELECTRICAL CHARACTER | 10/25/14 |
| A | INITIAL RELEASE | 08/20/14 |
| REV | DESCRIPTION OF CHANGE | DATE |

| TOLERANCE | | | | | | | | | |
|-----------|----------|-------|--|-------------------|-----|----------|-----|-------|---------|
| INCHES | M/M | | | | | | | SCALE | NONE |
| .X | .015 | .30 | | | | | | | |
| .XX | .010 | .10 | | UNIT | MM | | REV | C | |
| .XXX | .005 | .05 | | SHEET | 1/1 | | | | DWG NO. |
| DATE | 07/16/15 | TITLE | | DVI DF-DF-ADAPTER | | | | | |
| DRAWN BY | | LuLu | | PART NO. | | P162-000 | | | |
| CHECK BY | | | | | | | | | |
| APPD BY | | | | | | | | | |

