



Ordering Info for 115VAC versions



Delivery includes Fan tray assembly, molex power connector and mating pins.

Part Number	Description	Fan Specification
FT1U-3	3-Fans, 1.72"H x 19"W x 7.9"D	89 CFM, 52 dBA each fan
FT1U-6	6-Fans, 1.72"H x 19"W x 13.1"D	89 CFM, 52 dBA each fan
FT1U-9	9-Fans, 1.72"H x 19"W x 18.3"D	89 CFM, 52 dBA each fan



Part Number	Description	Fan Specification
FT1U-3AC	3-Fans, 1.72"H x 19"W x 7.9"D	70 CFM, 52 dBA each fan
FT1U-6AC	6-Fans, 1.72"H x 19"W x 13.1"D	70 CFM, 52 dBA each fan
FT1U-9AC	9-Fans, 1.72"H x 19"W x 18.3"D	70 CFM, 52 dBA each fan

Ordering Info for 12VDC versions

Delivery includes Fan tray assembly and 6' long 10A, 115VAC power cord.

Features

1U, 19" Rack-mountable Fan Trays

- 1U x 19", Rack-mountable per EIA-RS-310D
- Designed for high airflow performance
- Available in 3, 6 or 9 fan sizes
- Available with 115VAC or 12VDC input

Fan trays are designed as a cost effective solution, providing cooling as integral part of the rack equipment. Designed to operate at fixed speeds, the fans offer good reliability and performance in high density applications, providing an even airflow across the full cabinet width.

Fan trays are fully assembled, factory tested. All electrical components and finger guard covers are UL approved and recognized.