	D I	т (Г	D	0	B		
4	Z M Thread	ØF F F F F F F F F F F F F F F F F F F				4	
ယ				LAYOUT SHOWN AS EXAM	ЛРLE	3	
		Keying Shown as example					
	CHARACTERISTICSStandard : Based on MIL-DTL-38999 Series III	Connector dimension Dim Nominal E 22.25 Max]				
	-Shell Material: Aluminium-Shell Plating: Olive drab Cadmium-Insulator: Thermoplastic-Contacts: Copper Alloy	F22.25 MaxZ31.5 MaxVV THREADM18x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)			
N	-Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm minimum			Country FR	Jurisdiction & Control List Not Listed	2	
	-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories			PN: 8D113W08BA			
	-Temperature Range : -65°C to +175°C -Salt Spray : 500 hours		A 27-09-2	2016 First Release			
_			ISS DAT Designed By:	E Latest modification - by Date:	CUSTOMER DRAWING	10D N°	
			TITLE	Aluminium lı	nline plug 8D series		
	BASIC SERIES: 8D 1 - 13 W SHELL TYPE : In line Receptacle I	08 B A	SCALE	General linear Tolerances:	NPRDS / PROJECT 859		
	CONTACT TYPE : Standard Crimp Contact			SOURIAU This document is the property of SOURIAU It must not be reproduced or it must not be reproduced or			
	SHELL SIZE : 13 PLATING : W = Olive drab Cadmium	CONTACT TYPE : SOCKET(! CONTACT LA		SOURIAU D	communicated without permiss	ion SHEET	
			A3	8D113W08		1/2	
L	H G	F E	D	С	B A		

	Т	Q	т	п	D	0	ω	A		-
		Contact Layout								
4		$ \begin{array}{c} $								4
		Contact location X-axis (mm) Y-axis (mm) A +.065 (1.65) +.157 (3.99) B +.170 (4.32) +.000 (0.00) C +.120 (3.05) 120 (3.05) D ·.000 (0.00) 170 (4.32) E 120 (3.05) 120 (3.05) F 170 (4.32) +.000 (0.00) G 065 (1.65) +.157 (3.99) H +.000 (0.00) +.044 (1.12)								
ω	size no. c	Imber of Size Service Contact Supersedes ontacts contacts rating location 8 20 I All MS20051-8								3
						SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)				
N								n & Control List t Listed		2
						PN: 8D113W08BA				
						5 First Release				_
					ISS DATE Designed By:	Latest modification - by Date:	cu	STOMER DRAWING	MOD N°	
					TITLE	Alun	ninium Inline plug 8	D series		
<u> </u>					SCALE . NA	Genera Tolera ±	inces:	NPRDS / PROJECT 859 This document is the prop	erty of	1
					SOURIAU	SOURIAU WWW.SOURIAU.COM SOURIAU it must not be reproduce communicated without perroduce communicated without perroduce				
					FORMAT A3		RIAU DRG N° 13W08BA-C		SHEET 2/2	
	Н	G	F	E	D	C	B	A		