

Oct.1.2018 Copyright 2018 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
 In case that the application demands a high level of reliability, such as automotive,
 please contact a company representative for further information.

APPLICABLE STANDARD					
Rating	Operating Temperature Range	-25°C to +60°C	Storage Temperature Range	-25°C to +60°C	
	Voltage	—	Operating Humidity Range	—	
	Curent	—	Applicable Cable	—	
SPECIFICATIONS					
ITEM	TEST METHOD	REQUIREMENTS	QT	AT	
CONSTRUCTION					
General Examination	Visually and by measuring instrument.	According to drawing.	X	X	
Marking	Confirmed visually.		X	X	
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
①					
REMARK			APPROVED	NM. NISHIMATSU	17. 02. 07
			CHECKED	NM. NISHIMATSU	17. 02. 07
			DESIGNED	MO. SHIMOYAMA	17. 02. 07
			DRAWN	JY. IGA	17. 02. 07
Unless otherwise specified, refer to IEC 60512.					
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.	ELC-120682-06-00	
HRS	SPECIFICATION SHEET		PART NO.	TM11APA1-88P (06)	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL222-2783-4-06	⚠ 1/1