

APPLICATOR PARTS LIST

TYPE **LENGTHWISE AMPLIVAR
.250 SERIES FASTON TAB**

**AMP INCORPORATED
HARRISBURG, PENNA.**

NO.	DESCRIPTION	REQ.	PART NO.	NO.	DESCRIPTION	REQ.	PART NO.	CRIMPING DATA			TERMINALS		
								WIRE SIZE	CRIMP HEIGHT				
1	WIRE CRIMPER	1	455713-2	42				TO APPLY TERMINAL			62913		
2	INS. CRIMPER			43							62782		
3	ANVIL	1	463585-2	44				12	.113		62922		
4	ANVIL SPACER			45				13	.107		63016		
5	SHEAR BLADE	1	4465233-7	46				13 1/2	.105				
6	REAR SHEAR PLATE	1	385013-4	47				14	.103				
7	SHEAR BLADE SPACER	2	470931-2	48									
8	FRONT SHEAR PLATE	1	471422-1	49				CRIMP	SIZE	TYPE	FEED		
9	REAR ANVIL SPACER PLT.	1	472529-7	50				WIRE	.140	F			
10	FRONT ANVIL SPACER PLT.	1	470856-2	51				INSUL.	—	—	.909		
11	TOOL SPACER	1	370704	52				SLEEVED	—	—			
12	CRIMP SPACER			53	HOLD DOWN	1	811227-4	INSULATION RANGE				WIRE RANGE	
13	FRONT STRIP GUIDE	1	377723-1	54	SPACER - GUARD	2	385697	←			M-12 MAGNET		
14	REAR STRIP GUIDE	1	377723-2	55				EXPLODED VIEW				A-6000 A-6000-1	
15	RAM	1	471911	56				REMARKS:					
16	TOOL HOLDER			57									
17	ADJ. CRIMP MOUNT			58									
18	ADJ. BLOCK			59									
19	APPLICATOR MOUNT	1	471707-1	60									
20	BASE PLATE			61									
21	BASE BLOCK			62									
22	STRIP GUIDE PLATE			63									
23	ANVIL HOLDER			64									
24	AUX. ANVIL HOLDER			65	TENSION ADJ. PLATE	1	379999						
25	STRIPPER	1	454871-3	66	MISCELLANEOUS								
26	STRIPPER MOUNT	2	386231	67	AIR BLAST ASS'Y	1	455350-1						
27	RETAINER PLATE	2	372251	68	AIR BLAST TUBE	1	489446-2						
28	STRIPPER MOUNT BRACKET			69	BEARING THRUST	1	22217-3						
29	STRIPPER BUSHING			70	AIR FEED ASS'Y	1	460021-1						
30	STOCK DRAG	1	375381	71									
31	STOCK DRAG HANDLE			72									
32	STOCK DRAG STUD	2	354045-1	REV.	REVISION RECORD	DATE	BY	ECN	THIS APPLICATOR IS TO BE USED ON				
33	STOCK DRAG SPRING	2	1-23847-1	01	REV PER ECN	7-76	MB	R1751	AMP-O-ELECTRIC 1-471273-2			DIST. 4	
34	STOCK DRAG ADJ. SCREW	2	372997	02	REV PER ECN	1/1/76	MB	R1877	AMP-O-MATIC				
35	FEED FINGER HOLDER			03	ADD W/INSTR. ADD SY	4-24-76	MB	R2404	SERIAL NO.	DATE SHIPPED	DESIGNED		
36	FEED FINGER	1	375093	04	REV PER ECN	6-13-76	MB	R2565	CUSTOMER NAME AND ADDRESS			CHK'D	
37	FEED FINGER TIP			05	REV PER ECN	6-13-76	MB	R2641				3/76	
38	FEED FINGER SPACER			06	ADD TERM. 63016	3-31-80	MB	R3973				APPROV'D	
39	BASE CASTING	1	570233	07	REVISED PER ECN	7-21-81	MB	R4167				3/76	
40	GUARD	1	487664-7	08	ECN A-395892	9-92	MB		APPLICATOR NUMBER	REV. D	566221-1	SHEET 1 of 1	
41													

FOR HARDWARE SEE 1-687500-5