

Aug.1.2018 Copyright 2018 HIROSE ELECTRIC CO., LTD. All Rights Reserved.

Applicable standard		MIL-STD-348B		
Rating	Operating temperature range	$\Delta$ -55 °C to +125 °C ( 95 %RH Max.)	Storage temperature range	-20 °C to +70 °C ( 90 %RH Max.)
	Power	-- W	Characteristic impedance	50 $\Omega$ ( 0 to 30 GHz)
	Peculiarity	----	Applicable cable	----

**SPECIFICATIONS**

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
<b>CONSTRUCTION</b>				
General examination	Visually and by measuring instrument.	According to drawing.	X	X
Marking	Confirmed visually.		-	-

<b>ELECTRICAL CHARACTERISTICS</b>					
Contact resistance	100 mA (DC or 1000 Hz)	Center contact	6 m $\Omega$ Max.	X	X
		Outer contact	6 m $\Omega$ Max.	X	X
Insulation resistance	500 V DC.	1000 M $\Omega$ Min.		X	X
Withstanding voltage	500 V AC for 1 min. current leakage 2 mA Max.	No flashover or breakdown.		X	X
V.S.W.R.	Frequency 0 to 30 GHz.	V.S.W.R.	1.5 Max.	X	-
Insertion loss	Frequency - to - GHz.	--- dB Max.		-	-

<b>MECHANICAL CHARACTERISTICS</b>					
Contact insertion and extraction forces	$\phi$ --- by steel gauge.	Insertion force	--- N Max.	-	-
		Extraction force	--- N Min.	-	-
Insertion and extraction forces	Measured by applicable connector. [SMPJ-HKJ]	Insertion force	65 N Max.	X	X
		Extraction force	16 N Min.	X	X
Mechanical operation	100 times insertion and extractions.	1)Contact resistance: Center contact 12 m $\Omega$ Max. Outer contact 12 m $\Omega$ Max.		X	-
		2)No damage, crack and looseness of parts.			
Vibration	Frequency 10 to 500 Hz single amplitude 0.75 mm, 98 m/s <sup>2</sup> at 10 cycles for 3 directions.	1)No electrical discontinuity of 1 $\mu$ s.		X	-
		2)No damage, crack and looseness of parts.			
Shock	490 m/s <sup>2</sup> directions of pulse 11 ms at 3 times for 3 directions.			X	-
Cable clamp strength (against cable pull)	Using a pulling tester, pull the cable axially at a rate of --- mm/min. and record the strength at which the cable or connector breaks.	--- N Min.		-	-

<b>ENVIRONMENTAL CHARACTERISTICS</b>					
Temp heat	Exposed at +25 to +65 °C, 90 to 98 % total 10 cycles.(240h)	1)Insulation resistance: 100 M $\Omega$ Min. (at high humidity)		X	-
		2) Insulation resistance: 1000 M $\Omega$ Min. (at dry)			
		3)No damage, crack and looseness of parts.			
Rapid change of temperature	Temperature -55 $\rightarrow$ - $\rightarrow$ +125 $\rightarrow$ - °C Time 30 $\rightarrow$ 3 $\rightarrow$ 30 $\rightarrow$ 3 min. Under 5 cycles.	No damage, crack and looseness of parts.		X	-
Corrosion salt mist	Exposed in 5 % salt water spray for 48 h.	V.S.W.R.	1.5 Max. [0 to 30 GHz]	X	-

Count	Description of revisions	Designed	Checked	Date
$\Delta$ 1	DIS-D-00003210	TK.SAWAGUCHI	KY.SHIMIZU	18.06.07

Remark RoHS COMPLIANT Note $\Delta$ The characteristic after mounting on the board.	Approved	TO.KATAYAMA	17.09.05
	Checked	KY.SHIMIZU	17.09.05
	Designed	TK.SAWAGUCHI	17.09.05
	Drawn	TK.SAWAGUCHI	17.09.05

Unless otherwise specified, refer to IEC 60512.

Note QT:Qualification Test AT:Assurance Test X:Applicable Test

<b>HRS</b>	SPECIFICATION SHEET	Part No.	ELC-373487-00-00
	HIROSE ELECTRIC CO., LTD.	Code No.	SMP-PR(FD)-SMT-1 CL338-1102-0-00