



MATERIAL NO.	ENGINEERING NO.	ELECTRICAL RATING
1300190018	43301	VOLTAGE: 600VAC, CURRENT: 25 AMPS

ITEM	QTY.	DESCRIPTION	MATERIAL	FINISH
5	1	OVERMOLD	RUBBER	ORANGE
4	4	6-32 BINDING HD SCREW-.50 LG	STEEL	NICKEL PLATE
3	4	6-32 BINDING HD SCREW-.25 LG	BRASS	
2	1	SUPPORT PLATE	CRS	ZINC PLATE
1	4	SOCKET ASSEMBLY	BRASS	

NEW SALES DOC
 EC NO: IFC2013-0880
 DRAWN BY: DRWINRSTONE 2013/01/21
 CHECKED BY: JOZWIK 2013/01/25
 APPR: JFMURPHY 2013/03/01

QUALITY SYMBOLS
 ▼=0
 ▽=0

GENERAL TOLERANCES (UNLESS SPECIFIED)	
mm	INCH
4 PLACES ± .005	± .0004
3 PLACES ± .008	± .0003
2 PLACES ± .015	± .0006
1 PLACE ± .030	± .0012
0 PLACE ± .060	± .0024
ANGULAR ± 2 °	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	

DIMENSION STYLE	
IN/MM	DATE
DRAWN BY	RSTONE 2013/01/21
CHECKED BY	K. JOZWIK 2013/01/25
APPROVED BY	JFMURPHY 2013/03/01

SCALE 1:1 DESIGN UNITS INCH THIRD ANGLE PROJECTION

DIE BLOCK ANGLE RECEPTACLE FEMALE, 4 POLE-ORANGE

molex

MATERIAL NO. SEE CHART DOCUMENT NO. SD-130019-004 SHEET NO. 1 OF 1

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION